
Smart AC Charger

7.4kW






Product Advantages







IP55/65 Rating







Order Your Style









Smart APP

Full Protection





efficient charging experience. It can be realized with features like CE&UKCA certifications, full protection, Wi-Fi&Bluetooth connectivity, etc. Its DLB function and smart app

The Beny wall-mounted smart AC charger

is designed for reliable, convenient, and

Product Overview

also add to the intelligence.

Smart AC EV Charger

Electrical

Charging Capacity	1-phase
Charge Mode	Mode 3 (IEC 61851-1)
Output Power	7.4kW
Socket Type	Type 2
Tethered Cable Length	7m

Protection and certification

Build-in RCD	TYPE A + DC6mA leakage sensor built-in		
Protection Degree	IP65, IK10		
Housing Fire Ratings	V0		
Operating Temperature	-25°C~+55°C		
Compliance	IEC61851-1, IEC61851-21-2		
Certificate	CE, CB, UKCA		

Connectivity

Authorization	Auto-start standard / RFID card option
Status Indication	LED Lights
WLAN Communication	Wi-Fi / Bluetooth 4.2 option

Mechanical

Housing	Plastic
Dimension	W169 x H380 x D151/201 mm
Mounting	Wall or Pole

Model Selection

Smart AC EV Charger	BCP-A2N-L	
	8	
Categorization	Smart AC Charger	
Maximum Power	7.4kW	
Input Voltage /Output voltage	AC230 1-Phase	
Input Frequency	50/60Hz	
Meter	Metering Chip	
Display	LED Lights	
RFID	•	
DLB	0	
Wi-Fi	•	
APP	•	
Bluetooth	•	
Over Voltage &Under Voltage Protection	⊘	
Emergency Stop	•	
Over Current Protection	Ø	
CP Signal Short Circuit Protection	Ø	
Over Temperature Protection	•	
Lightning Protection	•	
Contactor Adhesion Protection	⊘	
Protection Degree	IP65	
Environment Temperature	-25°C~+55°C	
Maximun Altitude	<2000m	





